

AMENDMENTS TO THE CLAIMS

Claim 1 (Currently Amended) An ultrasound applicator for applying ultrasound energy to the thoracic cavity comprising

a housing sized for placement in acoustic contact with the thorax,

an ultrasound transducer carried by the housing comprising a transducer including a radiating surface to generate ultrasound energy at a prescribed fundamental therapeutic frequency laying within a range of fundamental therapeutic frequencies not exceeding about 500 kHz, and

an ultrasonic coupling region for the transducer carried by the housing being adapted, in use, to contact skin and being sized to transcutaneously conduct ultrasound energy in a diverging beam that substantially covers an entire heart, the coupling region including a coupling media, and

a well region surrounding the radiating surface and being located at a higher gravity plane than the radiating surface to collect air bubbles forming in the coupling media to minimize localized skin surface heating effects. and

~~an assembly worn on the thorax and adapted to be affixed to the housing, to stabilize placement of the housing on the thorax during transcutaneous conduction of ultrasound energy whereby the application of ultrasound energy increases the blood flow of the individual.~~

Claim 2 (Currently Amended) An ultrasound applicator for applying ultrasound energy to the thoracic cavity comprising

a housing sized for placement in acoustic contact with the thorax,

an ultrasound transducer including a radiating surface carried by the housing to generate ultrasound energy at a prescribed fundamental therapeutic frequency laying within a range of fundamental therapeutic frequencies not exceeding about 500 kHz, and

an ultrasonic coupling region for the transducer carried by the housing being adapted, in use, to contact skin and having an effective diameter (D) to transcutaneously conduct ultrasound energy at the prescribed fundamental therapeutic frequency by the transducer, the coupling region including a coupling media, and

the transducer having an aperture size (AP) not greater than about 5 wavelengths, wherein AP is expressed as $AP = D/WL$, where WL is the wavelength of the fundamental frequency, and

~~whereby the application of ultrasound energy increases the blood flow of the individual.~~

a well region surrounding the radiating surface and being located at a higher gravity plane than the radiating surface to collect air bubbles forming in the coupling media to minimize localized skin surface heating effects.

Claim 3 (Currently Amended) An ultrasound applicator according to claim 1 or 2

further including an assembly worn on the thorax and adapted to be affixed to the housing, to stabilize placement of the housing on the thorax during transcutaneous conduction of ultrasound energy.

Claim 4 (Original) An ultrasound applicator according to claim 1 or 2

wherein the range of fundamental therapeutic frequencies is between about 20 kHz and about 100kHz.

Claim 5 (Original) An ultrasound applicator according to claim 4

wherein the prescribed fundamental therapeutic frequency is about 27 kHz.

Claim 6 (Original) An ultrasound applicator according to claim 1 or 2

wherein the ultrasound transducer is sized to provide an intensity not exceeding 3 watts/cm² at a maximum total power output of no greater than 150 watts operating at the prescribed fundamental therapeutic frequency.

Claim 7 (Original) An ultrasound applicator according to claim 6

wherein the range of fundamental therapeutic frequencies is between about 20 kHz and about 100kHz.

Claim 8 (Original) An ultrasound applicator according to claim 7

wherein the prescribed fundamental therapeutic frequency is about 27 kHz.

Claim 9 (Original) An ultrasound applicator according to claim 1 or 2

wherein the housing is sized to allow another device to be placed on the thorax near the applicator.

Claim 10 (Original) An ultrasound applicator according to claim 9

wherein the device includes an ECG electrode device.

Claim 11 and 12(Canceled)

Claim 13 (Original) An ultrasound applicator according to claim 1 or 2

wherein the ultrasonic coupling region includes a flexible material that forms a contour-conforming interface with skin.

Claim 14 (Currently Amended) An ultrasound applicator according to claim 1 or 2

wherein the housing includes a skirt that enables spacing [a] the radiating surface of the ultrasound transducer from contact with skin.

Claim 15 (Currently Amended) A method for applying ultrasound energy to the thoracic cavity comprising the steps of

providing an ultrasound applicator ~~including a housing sized for placement on the thorax, an ultrasound transducer carried by the housing, and an ultrasonic coupling region carried by the housing~~ as defined in claim 1,

placing the ultrasonic coupling region in acoustic contact with skin on the thorax,

~~stabilizing the placement of the housing on the thorax,~~

operating the ultrasound transducer to generate ultrasound energy at a prescribed fundamental therapeutic frequency laying within a range of fundamental therapeutic frequencies not exceeding about 500 kHz, and

transcutaneously conducting the ultrasound energy through the ultrasonic coupling region in a diverging beam that substantially covers an entire heart, ~~whereby the application of ultrasound energy increases the blood flow of the individual.~~

Claim 16 (Currently Amended) A method for applying ultrasound energy to the thoracic cavity comprising the steps of

providing an ultrasound applicator ~~including a housing sized for placement in acoustic contact with the thorax, an ultrasound transducer carried by the housing, and an ultrasonic coupling region carried by the housing having an effective diameter (D)~~ as defined in claim 2,

placing the ultrasonic coupling region in acoustic contact with skin on the thorax,

operating the ultrasound transducer to generate ultrasound energy at a prescribed fundamental therapeutic frequency laying within a range of fundamental therapeutic frequencies not exceeding about 500 kHz, and

transcutaneously conducting the ultrasound energy through the ultrasonic coupling region at the prescribed fundamental therapeutic frequency;

wherein the transducer has an aperture size (AP) not greater than about 5 wavelengths, wherein AP is expressed as $AP = D/WL$, where WL is the wavelength of the fundamental frequency, whereby the application of ultrasound energy increases the blood flow of the individual.

Claim 17 (Currently Amended) A method according to claim 15 or 16

further including the step of stabilizing the placement of the housing on the thorax.

Claim 18 (Original) A method according to claim 15 or 16
wherein the housing is placed on the chest or near the sternum.

Claim 19 (Original) A method according to claim 15 or 16
wherein the range of fundamental therapeutic frequencies is between about 20 kHz and about 100kHz.

Claim 20 (Original) A method according to claim 19
wherein the prescribed fundamental therapeutic frequency is about 27 kHz.

Claim 21 (Original) A method according to claim 15 or 16
wherein the ultrasound transducer is operated to provide an intensity not exceeding 3 watts/cm² at a maximum total power output of no greater than 150 watts operating at the prescribed fundamental therapeutic frequency.

Claim 22 (Original) A method according to claim 21 wherein the range of fundamental therapeutic frequencies is between about 20 kHz and about 100kHz.

Claim 23 (Original) A method according to claim 22 wherein the prescribed fundamental therapeutic frequency is about 27 kHz.